



Technical details LLS75-GL Custom

Manufacturer	ALU+ limited
Type	<ul style="list-style-type: none">• Glazed-in louvre, with a pitch of 75mm.• All profiles are manufactured from aluminium extrusions.• Glazing thickness & rebate as required• Z-shaped louvre blades
Material	<ul style="list-style-type: none">• Aluminium - all parts (frame profile, clips and blades) are manufactured from aluminium extrusions Al Mg Si 0,5 (6063 T6)• Profile thickness: minimum 1.5mm. <p>Finish :</p> <ul style="list-style-type: none">• Natural anodised 15-22micron• Polyester powder coated - BS6496• Powder coating in any RAL or B/S colour available• Thickness of powder coating 40 micron minimum <p>Protection :</p> <ul style="list-style-type: none">• Fibre glass insect mesh fitted as standard.• Other meshes available as an option• A reinforcement profile carrying extra blade supports is fitted when the width of the louvre is > 1000mm.• Aluminium water drainage profile can be fitted at the bottom of the louvre to ensure better water tightness as an e/o
Manufacture	<ul style="list-style-type: none">• The aluminium louvre clips are fitted into the frame profile. The aluminium louvre blades are clipped into the louvre clips.• The blade height is 107mm & the visual free area is 71%.• Depth to fit 88mm
Assembly	Custom made by our skilled Craftsmen to your exact requirements

