

Technical details LLS75-SM (boxed frame)

Manufacturer	ALU+ limited
Type	<ul style="list-style-type: none"> • Box louvre, with a pitch of 75mm. • All profiles are manufactured from aluminium extrusions. • Z-shaped louvre blades
Material	<ul style="list-style-type: none"> • Aluminium - all parts (frame profile, clips and blades) are manufactured from aluminium extrusions Al Mg Si 0,5 (6063 T6) • Profile thickness: minimum 1.5mm. <p>Finish :</p> <ul style="list-style-type: none"> • Natural anodised 15-22micron • Polyester powder coated - BS6496 • Powder coating in any RAL or B/S colour available • Thickness of powder coating 40 micron minimum <p>Protection :</p> <ul style="list-style-type: none"> • Fibre glass insect mesh fitted as standard. • Other meshes available as an option • A reinforcement profile carrying extra blade supports is fitted when the width of the louvre is > 1000mm. • Aluminium water drainage profile can be fitted at the bottom of the louvre to ensure better water tightness as an e/o
Manufacture	<ul style="list-style-type: none"> • The louvre consists of a square box frame profile. • The aluminium louvre clips are fitted into the frame profile. The aluminium louvre blades are clipped into the louvre clips. • The blade height is 107mm & the visual free area is 71%. • Depth to fit 88mm
Assembly	Custom made by our skilled Craftsmen to your exact requirements

