

Technical details SLS34-SM

Manufacturer	ALU+ limited
Type	<ul style="list-style-type: none"> • Surface mounted louvre with a pitch of 34mm. • All profiles are manufactured from aluminium extrusions. • Z-shaped louvre blades.
Material	<ul style="list-style-type: none"> • Aluminium - all parts (frame profile, clips and blades) are manufactured from aluminium extrusions Al Mg Si 0,5 (6063 T6) • Profile thickness: minimum 1.0 mm. <p>Finish :</p> <ul style="list-style-type: none"> • Natural anodised 15-22micron • Polyester powder coated - BS6496 • Powder coating in any RAL or B/S colour available • Thickness of powder coating 40 micron minimum <p>Protection :</p> <ul style="list-style-type: none"> • Fibre glass insect mesh fitted as standard. • Other meshes available as an option • A reinforcement profile carrying extra blade supports is fitted when the width of the louvre is > 700mm. • Aluminium water drainage profile can be fitted at the bottom of the louvre to ensure better water tightness as an e/o
Manufacture	<ul style="list-style-type: none"> • The louvre consists of an angled box frame profile. • The aluminium louvre clips are glided into the frame profile. The aluminium louvre blades are clipped into the louvre clips. • The blade height is 39mm & the visual free area is 64%. • Depth to fit 35mm.
Assembly	Custom made by our skilled Craftsmen to your exact requirements

