

## Technical details LLS75-Cont

<b>Manufacturer</b>	ALU+ limited
<b>Type</b>	<ul style="list-style-type: none"> <li>• Continuous louvre system with a pitch of 75mm.</li> <li>• All profiles are manufactured from aluminium extrusions.</li> <li>• Z-shaped louvre blades.</li> <li>• Can be fitted to an existing construction and is supported by vertical mullions.</li> </ul>
<b>Material</b>	<ul style="list-style-type: none"> <li>• Aluminium - all parts (mullions, clips and blades) are manufactured from aluminium extrusions Al Mg Si 0,5 (6063 T6)</li> <li>• Profile thickness: minimum 1.5mm.</li> </ul> <p>Finish :</p> <ul style="list-style-type: none"> <li>• Natural anodised 15-22micron</li> <li>• Polyester powder coated - BS6496</li> <li>• Powder coating in any RAL or B/S colour available</li> <li>• Thickness of powder coating 40 micron minimum</li> </ul> <p>Protection :</p> <ul style="list-style-type: none"> <li>• Fibre glass insect mesh fitted as standard.</li> <li>• Other meshes available as an option</li> </ul>
<b>Manufacture</b>	<ul style="list-style-type: none"> <li>• Louvre consists of 2 upright mullions which hold the clips, an extra reinforcement mullion is added every 1000mm</li> <li>• Aluminium blade profiles are clipped into aluminium blade support clips.</li> <li>• The blade height is 107mm, the blade pitch is 75mm &amp; the visual free area is 71%.</li> </ul>
<b>Assembly</b>	Custom made by our skilled Craftsmen to your exact requirements

