

Technical details MLS50-GL Custom

Manufacturer	ALU+ limited
Type	<ul style="list-style-type: none"> • Glazed-in louvre, with a pitch of 50mm. • All profiles are manufactured from aluminium extrusions. • Available for a custom glazing thickness. • Z-shaped louvre blades
Material	<ul style="list-style-type: none"> • Aluminium - all parts (frame profile, clips and blades) are manufactured from aluminium extrusions Al Mg Si 0,5 (6063 T6) • Profile thickness: minimum 1.3mm. <p>Finish :</p> <ul style="list-style-type: none"> • Natural anodised 15-22micron • Polyester powder coated - BS6496 • Powder coating in any RAL or B/S colour available • Thickness of powder coating 40 micron minimum <p>Protection :</p> <ul style="list-style-type: none"> • Fibre glass insect mesh fitted as standard. • Stainless steel and gas meshes available as an option. • A reinforcement profile carrying extra blade supports is fitted when the width of the louvre is > 850mm. • Aluminium water drainage profile can be fitted at the bottom of the louvre to ensure better water tightness as an e/o
Manufacture	<ul style="list-style-type: none"> • The glazed-in louvre consists of a 19mm rebate. • The aluminium louvre clips are fitted into the frame profile. The aluminium louvre blades are clipped into the louvre clips. • The blade height is 73mm, & the visual free area is 66%. • Depth to fit 64.3mm
Assembly	Custom made by our skilled Craftsmen to your exact requirements

